



DARK STREET

REF	DESIGNATION	DARK STREET					HANDLING TUBE						SPACE BOOSTER				
		DS60	DS90	DS120	DS120W	DS150W	HT16-60	HT19-75	HT16-90	HT16-120	HT19-120	HT19-150	SB16-60	SB16-90	SB19-120	SB16-120W	SB19-150W
							DS60 DS120W	DS150W	DS90	DS120W	DS120	DS150W	DS60	DS90	DS120	DS120W	DS150W
T16-40	Pole Ø16 mm 360 mm																
T16-60	Pole Ø16 mm 560 mm	18			6		1					4				2	
T16-80	Pole Ø16 mm 760 mm																
T16-90	Pole Ø16 mm 860 mm		22		8			1					4				
T16-100	Pole Ø16 mm 960 mm	4															
T16-120	Pole Ø16 mm 1160 mm				8				1							2	
T16-Link	Link Ø16 mm	4	4		4												
C16-Y	Corner Ø16 mm 3 axes Y shape	8	8		8												
C16-K	Corner Ø16 mm 4 axes K shape																
C16-T	Corner Ø16 mm 3 axes T shape																
C16-XI	Corner Ø16 mm 5 axes XI shape																
C16-H	Handling Corner Ø16 mm	4	4		4		2		2	2							
C16-SB	Space Booster Ø16 mm	4	4		4							4	4		4		
C16-RF	Rubber Feet Ø16 mm																
T19-75	Pole Ø19 mm 726 mm					22					2						6
T19-100	Pole Ø19 mm 975 mm			8		8		1									
T19-120	Pole Ø19 mm 1153 mm			14						1				4			
T19-Link	Link Ø19 mm			4		12					1						2
C19-Y	Corner Ø19 mm 3 axes Y shape			8		8											
C19-K	Corner Ø19 mm 4 axes K shape																
C19-XI	Corner Ø19 mm 5 axes XI shape																
C19-H	Handling Corner Ø19 mm			4		4		2		2	2						
C19-SB	Space Booster Ø19 mm			4		4								4			4
C19-RF	Rubber Feet Ø19 mm																

REF	DESIGNATION	DARK ROOM					HANDLING TUBE		SPACE BOOSTER				SUPPORT IT	
		DR150	DR240	DR300	DR240W	DR300W	HT25-120	HT25-150	SB25-120	SB25-150	SB25-240W	SB25-300W	SPT25-200	SPT25-217
T25-60	Pole Ø25 mm 600 mm													
T25-75	Pole Ø25 mm 717 mm	30		84		52		2		8		12		
T25-100	Pole Ø25 mm 967 mm	4	18	9	12	6						2	1	
T25-120	Pole Ø25 mm 1134 mm	4	41	9	26	6	1		4		6		1	
T25-Link	Link Ø25 mm	19	9	51	6	32		1		4		6	1	1
C25-Y	Corner Ø25 mm 3 axes Y shape	8	8	8	8	8								
C25-K	Corner Ø25 mm 4 axes K shape		4	4	2	2								
C25-T	Corner Ø25 mm 3 axes T shape		4	4	2	2								
C25-XI	Corner Ø25 mm 5 axes XI shape		1	1										
C25-H	Handling Corner Ø25 mm	6	18	20	10	10	2	2						
C25-SB	Space Booster Ø25 mm	8	24	24	16	16			8	8	12	12		
C25-RF	Rubber Feet Ø25 mm		1	1									2	2

DARK ROOM

REF	DESIGNATION	INTENSE		HANDLING TUBE			SPACE BOOSTER		SUPPORT IT
		INT480	INT600	HT25-60	HT25-120	HT25-150	SB25-240W	SB25-300W	SPT25-235
T25-60	Pole Ø25 mm 600 mm	8	8	1					
T25-75	Pole Ø25 mm 717 mm		100			2		12	
T25-100	Pole Ø25 mm 967 mm								
T25-120	Pole Ø25 mm 1134 mm	90	40		1		6		2
T25-Link	Link Ø25 mm	20	70			1		6	1
C25-Y	Corner Ø25 mm 3 axes Y shape	8	8						
C25-K	Corner Ø25 mm 4 axes K shape	12	12						
C25-T	Corner Ø25 mm 3 axes T shape	10	10						
C25-XI	Corner Ø25 mm 5 axes XI shape	6	6						
C25-H	Handling Corner Ø25 mm	20	20	2	2	2			
C25-SB	Space Booster Ø25 mm						12	12	
C25-RF	Rubber Feet Ø25 mm	6	6						2

INTENSE



T16-40	360 MM
T16-60	560 MM
T16-80	760 MM
T16-90	860 MM
T16-100	960 MM
T16-120	1160 MM

POLES
Ø16 MM

T16-LINK
LINK


C16-Y
CORNER 3 AXES



C16-T
CORNER 3 AXES



C16-K
CORNER 4 AXES




C16-XI
CORNER 5 AXES



C16-H
HANDLING CORNER



C16-SB
SPACE BOOSTER



C16-RF
RUBBER FEET




T19-60	554 MM
T19-75	726 MM
T19-90	826 MM
T19-100	975 MM
T19-120	1152 MM
T19-LINK	LINK

POLES
Ø19 MM

C19-Y
CORNER 3 AXES



C19-K
CORNER 4 AXES



C19-XI
CORNER 5 AXES



C25-H
HANDLING CORNER



C25-SB
SPACE BOOSTER




C25-RF
RUBBER FEET



T25-60	600 MM
T25-75	717 MM
T25-100	967 MM
T25-120	1134 MM
T25-LINK	LINK

POLES
Ø25 MM


C25-Y
CORNER 3 AXES




C25-T
CORNER 3 AXES



C25-K
CORNER 4 AXES



C25-XI
CORNER 5 AXES



C25-H
HANDLING CORNER



C25-SB
SPACE BOOSTER



C25-RF
RUBBER FEET

