



# LODGE

# DARK PROPAGATOR

REF	DESIGNATION	LODGE		HANDLING TUBE			SPACE BOOSTER				DARK PROPAGATOR			HANDLING TUBE				SPACE BOOSTER		
		L100	L160	HT16-40	HT16-60	HT16-120	SB16-6040	SB16-12040	SB16-60	SB16-120	DP60	DP90	DP120	HT16-40	HT16-60	HT16-90	HT16-120	SB16-6040	SB16-9060	SB16-120W
T16-40	Pole Ø16 mm 360 mm	5	5	1			2	2		4	4	20	1				2			
T16-60	Pole Ø16 mm 560 mm	29			1		2		4	9	10	6		1			2			
T16-80	Pole Ø16 mm 760 mm																2			
T16-90	Pole Ø16 mm 860 mm										6				1			2		
T16-100	Pole Ø16 mm 960 mm	8	16																	
T16-120	Pole Ø16 mm 1160 mm		21			1		2	4			13				1			2	
T16-Link	Link Ø16 mm	4	4																	
C16-Y	Corner Ø16 mm 3 axes Y shape	16	16							8	8	8								
C16-K	Corner Ø16 mm 4 axes K shape	2	2									4								
C16-T	Corner Ø16 mm 3 axes T shape	2	2								4	12								
C16-XI	Corner Ø16 mm 5 axes XI shape																			
C16-H	Handling Corner Ø16 mm	6	6	2	2	2				2	4	2	2	2	2	2				
C16-SB	Space Booster Ø16 mm	4	4				4	4	4								4	4	4	
C16-RF	Rubber Feet Ø16 mm																			
GRID6040	Grid 60 x 40 cm	1	2							-	Option	12								

REF	DESIGNATION	HYDRO SHOOT				HANDLING POLE				SPACE BOOSTER			
		HS40	HS60	HS80	HS100	HT16-40	HT16-60	HT16-80	HT16-100	SB16-40	SB16-60	SB16-80	SB16-100
T16-40	Pole Ø16 mm 360 mm	10				1				4			
T16-60	Pole Ø16 mm 560 mm		10				1				4		
T16-80	Pole Ø16 mm 760 mm		8	10				1				4	
T16-90	Pole Ø16 mm 860 mm			8									
T16-100	Pole Ø16 mm 960 mm				18				1				4
T16-120	Pole Ø16 mm 1160 mm	4											
T16-Link	Link Ø16 mm		4	4	4								
C16-Y	Corner Ø16 mm 3 axes Y shape	8	8	8	8								
C16-K	Corner Ø16 mm 4 axes K shape												
C16-T	Corner Ø16 mm 3 axes T shape												
C16-XI	Corner Ø16 mm 5 axes XI shape												
C16-H	Handling Corner Ø16 mm	4	4	4	4	2	2	2	2				
C16-SB	Space Booster Ø16 mm									4	4	4	4
C16-RF	Rubber Feet Ø16 mm												

# HYDRO SHOOT SMALL

REF	DESIGNATION	HYDRO SHOOT								HANDLING POLE		SPACE BOOSTER				SUPPORT IT
		HS120	HS150	HS240	HS300	HS240W	HS300W	HS480W	HS600W	HT19-120	HT19-150	SB19-120	SB19-150	SB19-240W	SB19-300W	SP19-200
T19-75	Pole Ø19 mm 726 mm		20		50		32		92		2		8		12	
T19-100	Pole Ø19 mm 975 mm	8	8	18	18	12	12	30	30							2
T19-120	Pole Ø19 mm 1153 mm	10		25		16		46		1		4		6		
T19-Link	Link Ø19 mm	4	14	9	34	6	22	15	61		1		4		6	1
C19-Y	Corner Ø19 mm 3 axes Y shape	8	8	8	8	8	8	8	8							
C19-K	Corner Ø19 mm 4 axes K shape			8	8	4	4	16	16							
C19-XI	Corner Ø19 mm 5 axes XI shape			1	1			4	4							
C19-H	Handling Corner Ø19 mm	4	4	10	10	6	6	20	20	2	2					
C19-SB	Space Booster Ø19 mm											4	4	8	8	
C19-RF	Rubber Feet Ø19 mm			1	1			2	2							2

# HYDRO SHOOT LARGE



T16-40	360 MM
T16-60	560 MM
T16-80	760 MM
T16-90	860 MM
T16-100	960 MM
T16-120	1160 MM

**POLES**  
Ø16 MM

**T16-LINK**  
**LINK**



T19-60	554 MM
T19-75	726 MM
T19-90	826 MM
T19-100	975 MM
T19-120	1152 MM
T19-LINK	LINK

**POLES**  
Ø19 MM



T25-60	600 MM
T25-75	717 MM
T25-100	967 MM
T25-120	1134 MM
T25-LINK	LINK

**POLES**  
Ø25 MM

