



TECHNICAL DATA

SPECIFICATIONS

DARK STREET			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	DUCTING FLANGES INCLUDED				CABLE	HANDLING				ACCESSORIES					
REF	DESIGNATION	REV	Net lb	W in	D in	H in	Ø in	SUPPORT Included	TRAY Included	Support Flange	Connector #	Light Baffle #	Flange CF7 #	#	L in	Weight Per Pole	Weight Per Tent	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #		
DS60	Dark Street 2' x 2' x 62"	R4.00	14,8	24	24	62	0.63	1 WEBTH60	1 WTL60	2 DF16	2	-	-	1	1	2	24	20 lb	40 lb	1	1	15	1	-
DS90	Dark Street 3' x 3' x 70"	R4.00	19,8	35	35	70	0.63	1 WEBTH90	1 WTL90	2 DF16	2	-	-	1	1	2	35	20 lb	40 lb	1	1	15	1	-
DS120	Dark Street 4' x 4' x 79"	R4.00	32,2	47	47	79	0.75	1 WEBTH120	1 WTL120	2 DF16	-	-	2	1	1	2	47	30 lb	60 lb	1	1	15	1	-
DS120W	Dark Street 4' x 2' x 70"	R4.00	21,6	47	24	70	0.63	1 WEBTH120W	1 WTL120W	2 DF16	2	-	-	1	1	2	47	20 lb	40 lb	1	1	15	1	-
DS150W	Dark Street 5' x 2½' x 79"	R4.00	31,1	59	30	79	0.75	1 WEBTH150W	1 WTL150W	2 DF16	-	-	2	1	1	2	59	30 lb	60 lb	1	1	15	1	-

DARK ROOM			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	DUCTING FLANGES INCLUDED				CABLE	HANDLING				ACCESSORIES					
REF	DESIGNATION	REV	Net lb	W in	D in	H in	Ø in	SUPPORT Included	TRAY Included	Support Flange	Connector #	Light Baffle #	Flange CF7 #	#	L in	Weight Per Pole	Weight Per Tent	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #		
DR150	Dark Room 5' x 5' x 85"	R4.00	59	59	59	85	1.00	1 WEBIT150	1 WTL150	2 DF25	-	2	-	Option	2	3	59	50 lb	150 lb	1	1	20	1	-
DR240	Dark Room 8' x 8' x 79"	R4.00	102	93	93	79	1.00	2 WEBIT240W	2 WTL240W	2 DF25	-	-	2	Option	4	9	47	50 lb	450 lb	1	4	40	1	-
DR300	Dark Room 10' x 10' x 85"	R4.00	147	117	117	85	1.00	2 WEBIT300W	2 WTL300W	4 DF25	-	-	4	Option	4	10	59	50 lb	500 lb	2	4	40	1	-
DR240W	Dark Room 8' x 4' x 79"	R4.00	70	93	47	79	1.00	2 WEBIT120	1 WTL240W	2 DF25	-	2	-	Option	3	5	47	50 lb	250 lb	1	2	40	1	-
DR300W	Dark Room 10' x 5' x 85"	R4.00	95	117	59	85	1.00	2 WEBIT150	1 WTL300W	2 DF25	-	-	2	Option	3	5	59	50 lb	250 lb	1	2	40	1	-

INTENSE			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	DUCTING FLANGES INCLUDED				CABLE	HANDLING				ACCESSORIES					
REF	DESIGNATION	REV	Net lb	W in	D in	H in	Ø in	SUPPORT Option	TRAY Option	Mobile Ducting Flange Ø12½"	Ducting Flange	Connect. Ø10"	Light Baffle #	Flange CF7 #	#	L in	Weight Per Pole	Weight Per Room	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #	
INT480	Intense 16' x 10' x 92"	R4.00	194	118	185	92	1.00	4 WEBIT240W	4 WTL240W	2 DFM315	4 DF25	4	Option	5	10	47	50 lb	500 lb	2	8	60	2	-	-
INT600	Intense 20' x 12' x 92"	R4.00	247	142	232	92	1.00	4 WEBIT300W	4 WTL300W	2 DFM315	4 DF25	4	Option	5	10	59	50 lb	500 lb	2	8	60	2	-	-

DARK PROPAGATOR			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	DUCTING FLANGES INCLUDED				CABLE	HANDLING				ACCESSORIES					
REF	DESIGNATION	REV	Net lb	W in	D in	H in	Ø in	SUPPORT Included	TRAY Included	Support Flange	Connector #	Light Baffle #	Flange CF7 #	#	L in	Weight Per Pole	Weight Per Tent	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #		
DP60	Dark Propagator 2' x 1½' x 24"	R4.00	7,3	24	16	24	0.63		1 WT60.40	2 DF16	1	-	-	1	1	1	24	20 lb	20 lb	-	-	15	-	-
DP90	Dark Propagator 3' x 2' x 39"	R4.00	12,8	35	24	39	0.63		1 WT90.60	2 DF16	1	-	-	1	1	2	24	20 lb	40 lb	-	-	15	-	Option
DP120	Dark Propagator 4' x 2' x 75"	R4.00	43,7	47	24	75	0.63		1 WT120.60	2 DF16	1	-	-	1	2	1	47	20 lb	150 lb	-	-	30	-	12

LODGE			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	DUCTING FLANGES INCLUDED				CABLE	HANDLING				ACCESSORIES					
REF	DESIGNATION	REV	Net lb	W in	D in	H in	Ø in	Support Included	TRAY Included	Support Flange	Connector #	Light Baffle #	Flange CF7 #	#	L in	Weight Per Pole	Weight Per Tent	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #		
L100	Lodge 3½' x 2' x 62"	R4.00	29,8	39	24	62	0.63	1 WEBTH60	1 WT60	4 DF16	2	-	-	2	2	3	24	20 lb	60 lb	-	1	15	1	1
L160	Lodge 5¼' x 4' x 78"	R4.00	46,3	63	47	78	0.63	1 WEBTH120	1 WT120	4 DF16	1	-	1	2	2	3	47	20 lb	60 lb	-	1	15	1	2

HYDROSHOOT			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	SOCK CONFIGURATION				WINDOWS	HANDLING				ACCESSORIES					
REF	DESIGNATION	REV	Net lb	W in	D in	H in	Ø in	Support Option	TRAY Included	Ventilation Ø (in)	#	Cables Ø (in)	#	12" x 8" #	#	L in	Weight Per Pole	Weight Per Tent	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #	
HS40	Hydro Shoot 1½' x 1½' x 47"	R2.00	7,5	16	16	47	0.63	-	1 WT40	6	1	3	1	1	2	16	20 lb	40 lb	-	-	-	-	-	-
HS60	Hydro Shoot 2' x 2' x 62"	R2.00	10,6	24	24	62	0.63	1 WEBTH60	1 WT60	6	2	3	1	1	2	24	20 lb	40 lb	-	-	-	-	-	-
HS80	Hydro Shoot 2½' x 2½' x 70"	R2.00	13,4	32	32	70	0.63	-	1 WT80	7	2	3	1	1	2	32	20 lb	40 lb	-	-	-	-	-	-
HS100	Hydro Shoot 3½' x 3½' x 78"	R2.00	17,6	39	39	78	0.63	-	1 WT100	7	2	3	1	1	2	39	20 lb	40 lb	-	-	-	-	-	-
HS120	Hydro Shoot 4' x 4' x 79"	R2.00	20,9	47	47	79	0.75	1 WEBTH120	1 WT120	9	2	3	1	1	2	47	30 lb	60 lb	-	-	-	-	-	-
HS150	Hydro Shoot 5' x 5' x 79"	R2.00	28,7	59	59	79	0.75	1 WEBIT150	1 WT150	11	4	CF7D	1	-	2	59	30 lb	60 lb	-	-	-	-	-	-
HS240	Hydro Shoot 8' x 8' x 79"	R2.00	43,2	94	94	79	0.75	2 WEBIT240W	2 WT240W	15	4	CF7D	3	-	5	47	30 lb	150 lb	-	-	-	-	-	-
HS300	Hydro Shoot 10' x 10' x 79"	R2.00	58,2	117	117	79	0.75	2 WEBIT300W	2 WT300W	15	4	CF7D	3	-	5	59	30 lb	150 lb	-	-	-	-	-	-
HS240W	Hydro Shoot 8' x 4' x 79"	R2.00	38,4	94	47	79	0.75	1 WEBTH120	1 WT240W	11	4	CF7D	2	-	3	47	30 lb	90 lb	-	-	-	-	-	-
HS300W	Hydro Shoot 10' x 5' x 79"	R2.00	46,7	117	59	79	0.75	2 WEBIT150	1 WT300W	15	4	CF7D	2	-	3	59	30 lb	90 lb	-	-	-	-	-	-
HS480W	Hydro Shoot 16' x 8' x 79"	R2.00	95,9	186	94	79	0.75	4 WEBIT240W	4 WT240W	15	4	CF7D	4	-	10	47	30 lb	300 lb	-	-	-	-	-	-
HS600W	Hydro Shoot 20' x 10' x 79"	R2.00	123,5	234	117	79	0.75	4 WEBIT300W	4 WT300W	15	4	CF7D	4	-	10	59	30 lb	300 lb	-	-	-	-	-	-





TECHNICAL DATA

CONFIGURATION ADVISED

DARK STREET			MONKEY	LIGHTING ADVISED		VOL	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Level III LED PE2.7	Level II LED PE2.7	f13	1 min cycle		2 min cycle	
							Extraction	Intake	Extraction	Intake
DS60	Dark Street 2' x 2' x 62"	R4.00	1 MF16	100 W	60 W	21	90 cfm	-	50 cfm	-
DS90	Dark Street 3' x 3' x 70"	R4.00	1 MF16	200 W	100 W	53	150 cfm	-	90 cfm	-
DS120	Dark Street 4' x 4' x 79"	R4.00	1 MFO20	400 W	200 W	107	210 cfm	-	150 cfm	-
DS120W	Dark Street 4' x 2' x 70"	R4.00	1 MF16	200 W	100 W	47	150 cfm	-	90 cfm	-
DS150W	Dark Street 5' x 2½' x 79"	R4.00	1 MFO20	320 W	160 W	86	210 cfm	-	150 cfm	-

DARK ROOM			MONKEY	LIGHTING ADVISED		VOL	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Level III LED PE2.7	Level II LED PE2.7	f13	1 min cycle		2 min cycle	
							Extraction	Intake	Extraction	Intake
DR150	Dark Room 5' x 5' x 85"	R4.00	1 MFO20	600 W	400 W	181	400 cfm	50%	210 cfm	-
DR240	Dark Room 8' x 8' x 79"	R4.00	2 MF30	1600 W	800 W	416	550 cfm	50%	400 cfm	50%
DR300	Dark Room 10' x 10' x 85"	R4.00	2 MF30	2400 W	1600 W	709	700 cfm	50%	550 cfm	50%
DR240W	Dark Room 8' x 4' x 79"	R4.00	1 MF30	800 W	400 W	211	400 cfm	50%	210 cfm	-
DR300W	Dark Room 10' x 5' x 85"	R4.00	2 MF30	1200 W	800 W	358	550 cfm	50%	400 cfm	50%

INTENSE			MONKEY	LIGHTING ADVISED		VOL (*)	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Level III LED PE2.7	Level II LED PE2.7	f13	1 min cycle		2 min cycle	
							Extraction	Intake	Extraction	Intake
INT480	Intense 16' x 10' x 92"	R4.00	4 MF30	3200 W	1600 W	907	1100 cfm	50%	550 cfm	50%
INT600	Intense 20' x 12' x 92"	R4.00	4 MF30	4800 W	3200 W	1423	1450 cfm	50%	700 cfm	50%

DARK PROPAGATION			MONKEY	LIGHTING ADVISED / FLOOR		VOL	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Level II LED PE2.7	Level I LED PE2.0	f13	2 min cycle		4 min cycle	
							Extraction	Intake	Extraction	Intake
DP60	Dark Propagator 2' x 1½' x 24"	R4.00	-	40 W	20 W	5,3	30 cfm	-	6 cfm	-
DP90	Dark Propagator 3' x 2' x 39"	R4.00	-	80 W	40 W	20	50 cfm	-	12 cfm	-
DP120	Dark Propagator 4' x 2' x 75"	R4.00	-	80 W	40 W	51	90 cfm	-	30 cfm	-

LODGE			MONKEY	LIGHTING ADVISED		VOL	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Left Room LED PE2.7	Right Room LED PE2.0	f13	1 min cycle		2 min cycle	
							Extraction	Intake	Extraction	Intake
L100	Lodge 3½' x 2' x 62"	R4.00	1 MF16	100 W	20W / Floor	21	90 cfm	-	50 cfm	-
L160	Lodge 5¼' x 4' x 78"	R4.00	1 MFO20	400 W	40W / Floor	107	210 cfm	-	150 cfm	-

HYDROSHOOT			MONKEY	LIGHTING ADVISED		VOL	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Level III HPS	Level III LED PE2.7	f13	1 min cycle		2 min cycle	
							Extraction	Intake	Extraction	Intake
HS40	Hydro Shoot 1½' x 1½' x 47"	R2.00	-	-	-	7,1	30 cfm	-	20 cfm	-
HS60	Hydro Shoot 2' x 2' x 62"	R2.00	1 MF16	150 W	100 W	21	90 cfm	-	50 cfm	-
HS80	Hydro Shoot 2½' x 2½' x 70"	R2.00	1 MF16	250 W	180 W	42	120 cfm	-	90 cfm	-
HS100	Hydro Shoot 3½' x 3½' x 78"	R2.00	1 MF16	400 W	280 W	73	160 cfm	-	120 cfm	-
HS120	Hydro Shoot 4' x 4' x 79"	R2.00	1 MFO20	600 W	400 W	107	210 cfm	50%	150 cfm	50%
HS150	Hydro Shoot 5' x 5' x 79"	R2.00	1 MFO20	1000 W	600 W	167	400 cfm	50%	210 cfm	50%
HS240	Hydro Shoot 8' x 8' x 79"	R2.00	2 MF30	2400 W	1600 W	420	550 cfm	50%	400 cfm	50%
HS300	Hydro Shoot 10' x 10' x 79"	R2.00	2 MF30	4000 W	2400 W	658	700 cfm	50%	550 cfm	50%
HS240W	Hydro Shoot 8' x 4' x 79"	R2.00	1 MF30	1200 W	800 W	212	400 cfm	50%	210 cfm	50%
HS300W	Hydro Shoot 10' x 5' x 79"	R2.00	2 MF30	2000 W	1200 W	331	550 cfm	50%	400 cfm	50%
HS480W	Hydro Shoot 16' x 8' x 79"	R2.00	4 MF30	4800 W	3200 W	832	1100 cfm	50%	550 cfm	50%
HS600W	Hydro Shoot 20' x 10' x 79"	R2.00	4 MF30	8000 W	4800 W	1310	1450 cfm	50%	700 cfm	50%

🇬🇧 (*) Excluding central corridor (**) Without a filter, reduce by 40%. 🇫🇷 (*) Hors couloir central (**) Sans filtre, réduire de 40%.

🇪🇸 (*) Excluyendo el corredor central (**) Sin filtro, disminuir un 40%.

