



TECHNICAL DATA

SPECIFICATIONS

DARK STREET			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	DUCTING FLANGES INCLUDED				CABLE	HANDLING				ACCESSORIES					
REF	DESIGNATION	REV	Net kg	W cm	D cm	H cm	Ø mm	SUPPORT Included	TRAY Included	Support Flange	Connector #			Light Baffle #	Flange CF7 #	#	L cm	Weight Per Pole	Weight Per Tent	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #
DS60	Dark Street 60 x 60 x 158 cm	R4.00	6,7	60	60	158	16	1 WEBTH60	1 WTL60	2 DF16	2	-	-	1	1	2	60	10 kg	20 kg	1	1	15	1	-
DS90	Dark Street 90 x 90 x 178 cm	R4.00	9,0	90	90	178	16	1 WEBTH90	1 WTL90	2 DF16	-	2	-	1	1	2	90	10 kg	20 kg	1	1	15	1	-
DS120	Dark Street 120 x 120 x 200 cm	R4.00	14,6	120	120	200	19	1 WEBTH120	1 WTL120	2 DF16	-	-	2	1	1	2	120	15 kg	30 kg	1	1	15	1	-
DS120W	Dark Street 120 x 60 x 178 cm	R4.00	9,8	120	60	178	16	1 WEBTH120W	1 WTL120W	2 DF16	-	2	-	1	1	2	120	10 kg	20 kg	1	1	15	1	-
DS150W	Dark Street 150 x 77 x 200 cm	R4.00	14,1	150	77	200	19	1 WEBTH150W	1 WTL150W	2 DF16	-	-	2	1	1	2	150	15 kg	30 kg	1	1	15	1	-

DARK ROOM			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	DUCTING FLANGES INCLUDED				CABLE	HANDLING				ACCESSORIES					
REF	DESIGNATION	REV	Net kg	W cm	D cm	H cm	Ø mm	SUPPORT Included	TRAY Included	Support Flange	Connector #			Light Baffle #	Flange CF7 #	#	L cm	Weight Per Pole	Weight Per Tent	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #
DR150	Dark Room 150 x 150 x 217 cm	R4.00	26,8	150	150	217	25	1 WEBIT150	1 WTL150	2 DF25	-	2	-	Option	2	3	150	25 kg	75 kg	1	1	20	1	-
DR240	Dark Room 237 x 237 x 200 cm	R4.00	46,2	237	237	200	25	2 WEBIT240W	2 WTL240W	2 DF25	-	-	2	Option	4	9	120	25 kg	225 kg	1	4	40	1	-
DR300	Dark Room 297 x 297 x 217 cm	R4.00	66,6	297	297	217	25	2 WEBIT300W	2 WTL300W	4 DF25	-	-	4	Option	4	10	150	25 kg	250 kg	2	4	40	1	-
DR240W	Dark Room 237 x 120 x 200 cm	R4.00	31,7	237	120	200	25	2 WEBIT120	1 WTL240W	2 DF25	-	2	-	Option	3	5	120	25 kg	125 kg	1	2	40	1	-
DR300W	Dark Room 297 x 150 x 217 cm	R4.00	42,9	297	150	217	25	2 WEBIT150	1 WTL300W	2 DF25	-	-	2	Option	3	5	150	25 kg	125 kg	1	2	40	1	-

INTENSE			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	DUCTING FLANGES INCLUDED				CABLE	HANDLING				ACCESSORIES				
REF	DESIGNATION	REV	Net kg	W cm	D cm	H cm	Ø mm	SUPPORT Option	TRAY Option	Mobile Ducting Flange Ø315 mm	Ducting Flange	Connect. Ø250	Light Baffle #	Flange CF7 #	#	L cm	Weight / Pole	Weight / Room	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #
INT480	Intense 470 x 300 x 233 cm	R4.00	88	300	470	233	25	4 WEBIT240W	4 WTL240W	2 DFM315	4 DF25	4	Option	5	10	120	25 kg	250 kg	2	8	60	2	-
INT600	Intense 590 x 360 x 233 cm	R4.00	112	360	590	233	25	4 WEBIT300W	4 WTL300W	2 DFM315	4 DF25	4	Option	5	10	150	25 kg	250 kg	2	8	60	2	-

DARK PROPAGATOR			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	DUCTING FLANGES INCLUDED				CABLE	HANDLING				ACCESSORIES					
REF	DESIGNATION	REV	Net kg	W cm	D cm	H cm	Ø mm	SUPPORT	TRAY Included	Support Flange	Connector #			Light Baffle #	Flange CF7 #	#	L cm	Weight Per Pole	Weight Per Tent	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #
DP60	Dark Propagator 60 x 40 x 60 cm	R4.00	3,3	60	40	60	16	-	1 WT60.40	2 DF16	1	-	-	1	1	1	60	10 kg	10 kg	-	-	15	-	-
DP90	Dark Propagator 90 x 60 x 98 cm	R4.00	5,8	90	60	98	16	-	1 WT90.60	2 DF16	1	-	-	1	1	2	60	10 kg	20 kg	-	-	15	-	Option
DP120	Dark Propagator 120 x 60 x 190 cm	R4.00	19,8	120	60	190	16	-	1 WT120.60	2 DF16	1	-	-	1	2	1	120	10 kg	50 kg	-	-	30	-	12

LODGE			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	DUCTING FLANGES INCLUDED				CABLE	HANDLING				ACCESSORIES					
REF	DESIGNATION	REV	Net kg	W cm	D cm	H cm	Ø mm	Support Included	TRAY Included	Support Flange	Connector #			Light Baffle #	Flange CF7 #	#	L cm	Weight Per Pole	Weight Per Tent	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #
L100	Lodge 100 x 60 x 158 cm	R4.00	13,5	100	60	158	16	1 WEBTH60	1 WT60	4 DF16	2	-	-	2	2	3	60	10 kg	30 kg	-	1	15	1	1
L160	Lodge 160 x 120 x 198 cm	R4.00	21,0	160	120	198	16	1 WEBTH120	1 WT120	4 DF16	1	-	1	2	2	3	120	10 kg	30 kg	-	1	15	1	2

HYDROSHOOT			WGT	ASSEMBLED			POLES	WEB PLANT	WATER	SOCK CONFIGURATION				WINDOWS	HANDLING				ACCESSORIES				
REF	DESIGNATION	REV	Net kg	W cm	D cm	H cm	Ø mm	Support Option	TRAY Included	Ventilation Ø (mm)	#	Cables Ø (mm)	#	30 x 20 cm #	#	L cm	Weight Per Pole	Weight Per Tent	StrapIT Pair #	HookIT Pair #	CableIT #	PocketIT #	Grid6040 #
HS40	Hydro Shoot 40 x 40 x 120 cm	R2.00	3,4	40	40	120	16	-	1 WT40	150	1	75	1	1	2	40	10 kg	20 kg	-	-	-	-	-
HS60	Hydro Shoot 60 x 60 x 158 cm	R2.00	4,8	60	60	158	16	1 WEBTH60	1 WT60	150	2	75	1	1	2	60	10 kg	20 kg	-	-	-	-	-
HS80	Hydro Shoot 80 x 80 x 178 cm	R2.00	6,1	80	80	178	16	-	1 WT80	180	2	75	1	1	2	80	10 kg	20 kg	-	-	-	-	-
HS100	Hydro Shoot 100 x 100 x 198 cm	R2.00	8,0	100	100	198	16	-	1 WT100	180	2	75	1	1	2	100	10 kg	20 kg	-	-	-	-	-
HS120	Hydro Shoot 120 x 120 x 200 cm	R2.00	9,5	120	120	200	19	1 WEBTH120	1 WT120	230	2	75	1	1	2	120	15 kg	30 kg	-	-	-	-	-
HS150	Hydro Shoot 150 x 150 x 200 cm	R2.00	13,0	150	150	200	19	1 WEBIT150	1 WT150	280	4	CF7D	1	-	2	150	15 kg	30 kg	-	-	-	-	-
HS240	Hydro Shoot 238 x 238 x 200 cm	R2.00	19,6	238	238	200	19	2 WEBIT240W	2 WT240W	380	4	CF7D	3	-	5	120	15 kg	75 kg	-	-	-	-	-
HS300	Hydro Shoot 298 x 298 x 200 cm	R2.00	26,4	298	298	200	19	2 WEBIT300W	2 WT300W	380	4	CF7D	3	-	5	150	15 kg	75 kg	-	-	-	-	-
HS240W	Hydro Shoot 238 x 120 x 200 cm	R2.00	17,4	238	120	200	19	2 WEBIT120	1 WT240W	280	4	CF7D	2	-	3	120	15 kg	45 kg	-	-	-	-	-
HS300W	Hydro Shoot 298 x 150 x 200 cm	R2.00	21,2	298	150	200	19	2 WEBIT150	1 WT300W	380	4	CF7D	2	-	3	150	15 kg	45 kg	-	-	-	-	-
HS480W	Hydro Shoot 472 x 238 x 200 cm	R2.00	43,5	472	238	200	19	4 WEBIT240W	4 WT240W	380	4	CF7D	4	-	10	120	15 kg	150 kg	-	-	-	-	-
HS600W	Hydro Shoot 594 x 298 x 200 cm	R2.00	56,0	593	298	200	19	4 WEBIT300W	4 WT300W	380	4	CF7D	4	-	10	150	15 kg	150 kg	-	-	-	-	-





TECHNICAL DATA

CONFIGURATION ADVISED

DARK STREET			MONKEY	LIGHTING ADVISED		VOL	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Level III LED PE2.7	Level II LED PE2.7	m3	1 min cycle		2 min cycle	
							Extraction	Intake	Extraction	Intake
DS60	Dark Street 60 x 60 x 158 cm	R4.00	1 MF16	100 W	40 W	0,6	150 m3/h	-	80 m3/h	-
DS90	Dark Street 90 x 90 x 178 cm	R4.00	1 MF16	200 W	100 W	1,4	250 m3/h	-	150 m3/h	-
DS120	Dark Street 120 x 120 x 200 cm	R4.00	1 MFO20	400 W	200 W	2,9	350 m3/h	-	250 m3/h	-
DS120W	Dark Street 120 x 60 x 178 cm	R4.00	1 MF16	200 W	100 W	1,3	250 m3/h	-	150 m3/h	-
DS150W	Dark Street 150 x 77 x 200 cm	R4.00	1 MFO20	320 W	160 W	2,3	350 m3/h	-	250 m3/h	-

DARK ROOM			MONKEY	LIGHTING ADVISED		VOL	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Level III LED PE2.7	Level II LED PE2.7	m3	1 min cycle		2 min cycle	
							Extraction	Intake	Extraction	Intake
DR150	Dark Room 150 x 150 x 217 cm	R4.00	1 MFO20	600 W	400 W	4,9	650 m3/h	50%	350 m3/h	-
DR240	Dark Room 237 x 237 x 200 cm	R4.00	2 MF30	1600 W	800 W	11,2	900 m3/h	50%	650 m3/h	50%
DR300	Dark Room 297 x 297 x 217 cm	R4.00	2 MF30	2400 W	1600 W	19,1	1200 m3/h	50%	900 m3/h	50%
DR240W	Dark Room 237 x 120 x 200 cm	R4.00	1 MF30	800 W	400 W	5,7	650 m3/h	50%	350 m3/h	-
DR300W	Dark Room 297 x 150 x 217 cm	R4.00	2 MF30	1200 W	800 W	9,7	900 m3/h	50%	600 m3/h	50%

INTENSE			MONKEY	LIGHTING ADVISED		VOL (*)	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Level III LED PE2.7	Level II LED PE2.7	m3	1 min cycle		2 min cycle	
							Extraction	Intake	Extraction	Intake
INT480	Intense 470 x 300 x 233 cm	R4.00	4 MF30	3200 W	1600 W	24,5	1800 m3/h	50%	900 m3/h	50%
INT600	Intense 590 x 360 x 233 cm	R4.00	4 MF30	4800 W	3200 W	38,4	2400 m3/h	50%	1200 m3/h	50%

DARK PROPAGATOR			MONKEY	LIGHTING ADVISED / FLOOR		VOL	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Level II LED PE2.0	Level I LED PE2.0	m3	2 min cycle		4 min cycle	
							Extraction	Intake	Extraction	Intake
DP60	Dark Propagator 60 x 40 x 60 cm	R4.00	-	40 W	20 W	0,1	50 m3/h	-	10 m3/h	-
DP90	Dark Propagator 90 x 60 x 98 cm	R4.00	-	80 W	40 W	0,5	80 m3/h	-	20 m3/h	-
DP120	Dark Propagator 120 x 60 x 190 cm	R4.00	-	80 W	40 W	1,4	150 m3/h	-	50 m3/h	-

LODGE			MONKEY	LIGHTING ADVISED		VOL	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Left Room LED PE2.7	Right Room LED PE2.0	m3	1 min cycle		2 min cycle	
							Extraction	Intake	Extraction	Intake
L100	Lodge 100 x 60 x 158 cm	R4.00	1 MF16	100 W	20W / Floor	0,6	150 m3/h	-	80 m3/h	-
L160	Lodge 160 x 120 x 198 cm	R4.00	1 MFO20	400 W	40W / Floor	2,9	350 m3/h	-	250 m3/h	-

HYDROSHOOT			MONKEY	LIGHTING ADVISED		VOL	EXTRACTOR ADVISED WHEN FILTER ON (**)			
REF	DESIGNATION	REV	FAN Advised	Level III HPS	Level III LED PE2.7	m3	1 min cycle		2 min cycle	
							Extraction	Intake	Extraction	Intake
HS40	Hydro Shoot 40 x 40 x 120 cm	R2.00	-	-	-	0,2	50 m3/h	-	30 m3/h	-
HS60	Hydro Shoot 60 x 60 x 158 cm	R2.00	1 MF16	150 W	100 W	0,6	150 m3/h	-	80 m3/h	-
HS80	Hydro Shoot 80 x 80 x 178 cm	R2.00	1 MF16	250 W	180 W	1,1	200 m3/h	-	150 m3/h	-
HS100	Hydro Shoot 100 x 100 x 198 cm	R2.00	1 MF16	400 W	280 W	2,0	270 m3/h	-	200 m3/h	-
HS120	Hydro Shoot 120 x 120 x 200 cm	R2.00	1 MFO20	600 W	400 W	2,9	350 m3/h	50%	250 m3/h	50%
HS150	Hydro Shoot 150 x 150 x 200 cm	R2.00	1 MFO20	1000 W	600 W	4,5	650 m3/h	50%	350 m3/h	50%
HS240	Hydro Shoot 238 x 238 x 200 cm	R2.00	2 MF30	2400 W	1600 W	11,3	900 m3/h	50%	650 m3/h	50%
HS300	Hydro Shoot 298 x 298 x 200 cm	R2.00	2 MF30	4000 W	2400 W	17,8	1200 m3/h	50%	900 m3/h	50%
HS240W	Hydro Shoot 238 x 120 x 200 cm	R2.00	1 MF30	1200 W	800 W	5,7	650 m3/h	50%	350 m3/h	50%
HS300W	Hydro Shoot 298 x 150 x 200 cm	R2.00	2 MF30	2000 W	1200 W	8,9	900 m3/h	50%	650 m3/h	50%
HS480W	Hydro Shoot 472 x 238 x 200 cm	R2.00	4 MF30	4800 W	3200 W	22,5	1800 m3/h	50%	900 m3/h	50%
HS600W	Hydro Shoot 594 x 298 x 200 cm	R2.00	4 MF30	8000 W	4800 W	35,4	2400 m3/h	50%	1200 m3/h	50%

