

	T16-40	360 mm
	T16-60	560 mm
	T16-80	760 mm
	T16-90	860 mm
	T16-100	960 mm
	T16-120	1160 mm

POLES Ø16 mm	C16-Y	CORNER 3 AXES
T16-LINK	LINK	

C16-T	C16-K
CORNER 3 AXES	CORNER 4 AXES

C16-XI	C16-H
CORNER 5 AXES	HANDLING CORNER

C16-SB	C16-RF
SPACE BOOSTER	RUBBER FEET

	T19-75	726 mm
	T19-100	975 mm
	T19-120	1152 mm
	T19-LINK	LINK

POLES Ø19 mm	C19-Y	CORNER 3 AXES
C19-K	CORNER 4 AXES	

C19-XI	C19-H
CORNER 5 AXES	HANDLING CORNER

C19-SB	C19-RF
SPACE BOOSTER	RUBBER FEET

	T25-60	600 mm
	T25-75	717 mm
	T25-100	967 mm
	T25-120	1134 mm
	T25-LINK	LINK

POLES Ø25 mm	C25-Y	CORNER 3 AXES
C25-K	CORNER 4 AXES	

C25-XI	C25-H
CORNER 5 AXES	HANDLING CORNER

C25-SB	C25-RF
SPACE BOOSTER	RUBBER FEET



DARK STREET

REF	DESIGNATION	STRUCTURE					HANDLING POLES INCLUDED					SPACE BOOSTER INCLUDED				
		DS60	DS90	DS120	DS120W	DS150W	DS60	DS90	DS120	DS120W	DS150W	DS60	DS90	DS120	DS120W	DS150W
T16-60	Pole Ø16 mm 560 mm	12			4		2					4				2
T16-90	Pole Ø16 mm 860 mm		16		8			2					4			
T16-100	Pole Ø16 mm 960 mm	4														
T16-120	Pole Ø16 mm 1160 mm				4					2						2
T16-Link	Link Ø16 mm	4	4		4											
C16-Y	Corner Ø16 mm 3 axes Y shape	8	8		8											
C16-H	Handling Corner Ø16 mm					2	4			2						
C16-SB	Space Booster Ø16 mm										4	4			4	
T19-75	Pole Ø19 mm 726 mm					12					4					6
T19-100	Pole Ø19 mm 975 mm				8											
T19-120	Pole Ø19 mm 1153 mm				8				2					4		
T19-Link	Link Ø19 mm				4						2					2
C19-Y	Corner Ø19 mm 3 axes Y shape				8											
C19-H	Handling Corner Ø19 mm								4			4				
C19-SB	Space Booster Ø19 mm													4		4

DARK ROOM

REF	DESIGNATION	STRUCTURE					HANDLING POLES INCLUDED					SPACE BOOSTER INCLUDED				
		DR150	DR240	DR300	DR240W	DR300W	DR150	DR240	DR300	DR240W	DR300W	DR150	DR240	DR300	DR240W	DR300W
T25-75	Pole Ø25 mm 717 mm	16		40		26	6		20		10	8		24		16
T25-100	Pole Ø25 mm 967 mm	4	18	9	12	6										
T25-120	Pole Ø25 mm 1134 mm	4	20	9	13	6		9		5			12		8	
T25-Link	Link Ø25 mm	12	9	29	6	19	3		10		5	4		12		8
C25-Y	Corner Ø25 mm 3 axes Y shape	8	8	8	8	8										
C25-K	Corner Ø25 mm 4 axes K shape		4	4	2	2										
C25-T	Corner Ø25 mm 3 axes T shape		4	4	2	2										
C25-XI	Corner Ø25 mm 5 axes XI shape		1	1												
C25-H	Handling Corner Ø25 mm						6	18	20	10	10					
C25-SB	Space Booster Ø25 mm											8	24	24	16	16
C25-RF	Rubber Feet Ø25 mm		1	1												

HYDRO SHOOT (SMALL)

REF	DESIGNATION	STRUCTURE				HANDLING POLES INCLUDED			
		HS40	HS60	HS80	HS100	HS40	HS60	HS80	HS100
T16-40	Pole Ø16 mm 360 mm	8				2			
T16-60	Pole Ø16 mm 560 mm		8				2		
T16-80	Pole Ø16 mm 760 mm		8	8				2	
T16-90	Pole Ø16 mm 860 mm			8					
T16-100	Pole Ø16 mm 960 mm				16				2
T16-120	Pole Ø16 mm 1160 mm	4							
T16-Link	Link Ø16 mm		4	4	4				
C16-Y	Corner Ø16 mm 3 axes Y shape	8	8	8	8				
C16-H	Handling Corner Ø16 mm					4	4	4	4

HYDRO SHOOT (LARGE)

REF	DESIGNATION	STRUCTURE								HANDLING POLES INCLUDED							
		HS120	HS150	HS240	HS300	HS240W	HS300W	HS480W	HS600W	HS120	HS150	HS240	HS300	HS240W	HS300W	HS480W	HS600W
T19-75	Pole Ø19 mm 726 mm		16		40		26		72								20
T19-100	Pole Ø19 mm 975 mm	8	8	18	18	12	12	30	30								
T19-120	Pole Ø19 mm 1153 mm	8		20		13		36									
T19-Link	Link Ø19 mm	4	12	9	29	6	19	15	51								10
C19-Y	Corner Ø19 mm 3 axes Y shape	8	8	8	8	8	8	8	8								
C19-K	Corner Ø19 mm 4 axes K shape			8	8	4	4	16	16								
C19-XI	Corner Ø19 mm 5 axes XI shape			1	1			4	4								
C19-H	Handling Corner Ø19 mm									4	4	10	10	6	6	20	20
C19-RF	Rubber Feet Ø19 mm			1	1			2	2								

DARK PROPAGATOR

REF	DESIGNATION	STRUCTURE			HANDLING POLES		
		DP60	DP90	DP120	DP60	DP90	DP120
T16-40	Pole Ø16 mm 360 mm	4	4	20			
T16-60	Pole Ø16 mm 560 mm	8	8	6	1	2	
T16-90	Pole Ø16 mm 860 mm		6				
T16-120	Pole Ø16 mm 1160 mm			12			1
C16-Y	Corner Ø16 mm 3 axes Y shape	8	8	8			
C16-K	Corner Ø16 mm 4 axes K shape			4			
C16-T	Corner Ø16 mm 3 axes T shape		4	12			
C16-H	Handling Corner Ø16 mm				2	2	2
GRID6040	Grid 60 x 40 cm	-	Option	12			

LODGE

REF	DESIGNATION	STRUCTURE		HANDLING POLES INC.		SPACE BOOSTER INC.	
		L100	L160	L100	L160	L100	L160
T16-40	Pole Ø16 mm 360 mm	5	5				
T16-60	Pole Ø16 mm 560 mm	22		3		4	
T16-100	Pole Ø16 mm 960 mm	8	16				
T16-120	Pole Ø16 mm 1160 mm		14		3		4
T16-Link	Link Ø16 mm	4					
C16-Y	Corner Ø16 mm 3 axes Y shape	16	16				
C16-K	Corner Ø16 mm 4 axes K shape	2	2				
C16-T	Corner Ø16 mm 3 axes T shape	2	2				
C16-H	Handling Corner Ø16 mm			6	6		
C16-SB	Space Booster Ø16 mm					4	4
GRID6040	Grid 60 x 40 cm	1	2				

INTENSE

REF	DESIGNATION	STRUCTURE		HANDLING POLES INC.		SPACE BOOSTER INC.	
		INT480	INT600	INT480	INT600	INT480	INT600
T25-60	Pole Ø25 mm 600 mm	8	8				
T25-75	Pole Ø25 mm 717 mm		80		20		48
T25-120	Pole Ø25 mm 1134 mm	80	40	10		24	
T25-Link	Link Ø25 mm	20	60		10		24
C25-Y	Corner Ø25 mm 3 axes Y shape	8	8				
C25-K	Corner Ø25 mm 4 axes K shape	12	12				
C25-T	Corner Ø25 mm 3 axes T shape	10	10				
C25-XI	Corner Ø25 mm 5 axes XI shape	6	6				
C25-H	Handling Corner Ø25 mm			20	20		
C25-SB	Space Booster Ø25 mm					48	48
C25-RF	Rubber Feet Ø25 mm	6	6				